

Application

A ground mounted LED luminaire with low mounting height and 360° light distribution. The narrow beam light distribution is ideally suited for illuminating and grazing ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Borosilicate glass lens  
Clear glass optical collimator  
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 67  
Weight: 10.8lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	18.1 W
System wattage	21.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	506 lumens (3000K)
Lifetime at Ta = 15° C	400,000 h (L70)
Lifetime at Ta = 45° C	220,000 h (L70)

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



Ground mounted luminaire - 360° light distribution				
	LED	A	B	Anchorage
88363	18.1 W	9	9	79815

Type:  
BEGA Product:  
Project:  
Modified:

