

Type:  
Project:  
Options:  
Modified:  
Luminaire:  
Fixture EPA:

Approval:

## 928 Tapered round base pole

**Wall thickness:** .125"

**Shaft:** Extruded from all new seamless 6063 aluminum alloy tubing, heat treated to a T-6 condition.

**Bell base:** Round cast aluminum A356 alloy, heat treated to a T-6 condition. Anchor base and shaft continuously welded internally - no exposed welds..

**Anchor base:** Internal anchor base casting accepts bell base of pole. Four (4) socket head stainless steel bolts threaded into stainless steel inserts retain pole.

**Access door:** Flush, covered wiring access holesis provided, centered 27 $\frac{3}{8}$ " above base. Opening is 4" x 11 $\frac{1}{4}$ ".

**Anchorage:** Supplied with 8986A anchorage.

**GCO or GFI:** Standard GCO/GFI location inside the handhole.

### Disclaimer

BEGA-US warrants the specific anchor bolts and pole combination according to the product number(s) and description(s) indicated on this submittal sheet. Structural changes to the pole requested by the customer, including changes to pole length, may affect the compatibility of the anchor bolts and corresponding poles. BEGA-US is not responsible for the incompatibility of the anchor bolts and poles resulting from such structural changes without review by the BEGA-US engineering department. This includes, but is not limited to, any labor charges, charges for replacement materials and shipping.

Pole wind load rating:

MPH: 70 80 90 100 120

EPA: 16.2 11.9 9.0 7.1 4.6

**Note:** Data above assumes grade level installation and a maximum luminaire weight of 50 lbs.

**BEGA-US** 1000 BEGA Way, Carpinteria, CA 93013 [P] 805-684-0533 [F] 805-684-6682

©Copyright BEGA-US 2012 updated 03/2019

