

Application

Designed for effective lighting of pathways, entrances and driveways and for wayfinding. Provided with signage complete with individual lettering, symbols, or logos, consult factory for details.

Materials

Luminaire housing constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Signage constructed of extruded aluminum, height depends on specified lettering (consult factory)
 White safety glass
 Mechanically captive stainless steel fasteners
 Anchorage constructed of galvanized steel

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 127.9lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	47.2W
System wattage	55.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	3661 lumens (3000K)
Lifetime at Ta = 15° C	100,000 h (L70)
Lifetime at Ta = 35° C	75,000 h (L70)

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED indication luminaire · externally illuminated sign

	LED	A	B	C	D
99069	47.2W	69	39%	23 1/4	7

Type:
 BEGA Product:
 Project:
 Modified:

