


# BEGA



Photometric Filename: 99447.IES

TEST: BE\_99446  
 TEST LAB: BEGA  
 DATE: 8/23/2016  
 LUMINAIRE: 99 447  
 LAMP: (2) 11.8W LED

\*Report based on a single IES file, see below for  
 twin head iso-footcandle template




## Characteristics

IES Classification	Type II
Longitudinal Classification	Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1739
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	109
Total Luminaire Watts	16
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Max. Cd.	908 (300H, 55V)
Max. Cd. (<90 Vert.)	908 (300H, 55V)
Max. Cd. (At 90 Deg. Vert.)	0 (0.0%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	176.6 (10.2%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


## Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	175.9	N.A.	10.1
FM (30-60)	687.8	N.A.	39.6
FH (60-80)	317.5	N.A.	18.3
FVH (80-90)	14.0	N.A.	0.8
BL (0-30)	131.6	N.A.	7.6
BM (30-60)	296.3	N.A.	17.0
BH (60-80)	112.3	N.A.	6.5
BVH (80-90)	3.6	N.A.	0.2
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	1739.0	N.A.	100.0

BUG Rating B1-U0-G1



Mounting Height = 16 ft.  
 Grid Spacing = 15 ft.  
 (Pole 916HR)



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

3/22/2018