Application

LED pole-top luminaire with asymmetrical flat beam light distribution designed for the illumination of parking areas and roadways. Tool-less entry with hinged door for ease of maintenance. Provided with slip fitter to fit 3" O.D. poles.

Materials

Luminaire housing and pole fitter constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Clear safety glass with anti-reflective coating for increased transmission Reflector made of pure anodized aluminum

Silicone applied robotically to casting, plasma treated for increased adhesion

High temperature silicone gasket

Mechanically captive stainless steel fasteners

 $\mbox{\bf NRTL}$ listed to North American Standards, suitable for wet locations Protection class IP 66

Weight: 9.7 lbs.

EPA (Effective projection area): 0.32 sq. ft.

Electrical

Operating voltage 120-277V AC Minimum start temperature -30° C LED module wattage 23.6 W System wattage 29.0 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 80

 $\begin{array}{lll} \mbox{Luminaire lumens} & 3,492 \mbox{ lumens (3000K)} \\ \mbox{Lifetime at Ta=15°C} & >500,000 \mbox{ h (L70)} \\ \mbox{Lifetime at Ta=45°C} & 308,000 \mbox{ h (L70)} \\ \end{array}$

LED color temperature

400K - Product number + **K4** 3500K - Product number + **K35** 3000K - Product number + **K3** 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) White (WHT) RAL:
Bronze (BRZ) Silver (SLV) CUS:

Type:

BEGA Product:

Project:

Modified:





Pole-top luminaire · Asymmetrical flat beam				
	LED	А	В	С
99 499	23.6W	10	2 3/8	173/8

Recommended for use with 15' to 20' poles