

BEGA LED system bollard - bollard tube for luminaire height 43 1/4

**Post construction:** One piece extruded aluminum, 3/16" wall thickness with a one peice base, internally welded into an assembly. Provided with access door. Die castings are marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy. Designed to accept BEGA LED system bollard heads of 10 3/8" in diameter.

**Anchor base:** Heavy cast aluminum, slotted for precise alignment. Mounts to BEGA 79 818 anchorage kit. Bollard secures to base with one stainless steel set screw. The mounting system allows the luminaire to be adjusted independent of anchor bolt orientation.

**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

**Note:** See below for compatible LED system bollard heads. See specifications for details.

**CSA** certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

**Weight:** 24.5 lbs.

Type:  
BEGA Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:




99 777



99 778



99 865



Bollard tubes for luminaire heights 31 1/2 · 39 1/4 · 43 1/4				
	Door	A	B	Anch. unit
99 624	✓	10 3/8	34 1/2	79 818