

BEGA LED system bollard - bollard tube for luminaire height 39 1/4 with integrated emergency lighting battery

**Post construction:** One piece extruded aluminum, 3/16" wall thickness with a one peice base, internally welded into an assembly. Die castings are marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy. Designed to accept BEGA LED system bollard heads of 7 1/2" in diameter.

**Integrated components:** Bollard tube provided with integrated emergency lighting battery 6.0W. Battery will operate fixture at 42% of full output for 90 minutes. Ambient temperature must not go below -20°C and must not exceed 55°C. Specify input voltage - 120V or 277VAC


**Anchor base:** Heavy cast aluminum, slotted for precise alignment. Mounts to BEGA 79 818 anchorage kit. Bollard secures to base with one stainless steel set screw. The mounting system allows the luminaire to be adjusted independent of anchor bolt orientation.

**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

**Note:** See below for compatible LED system bollard heads. See specifications for details.

**CSA** certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

**Weight:** 18.7 lbs.



Bollard tubes for luminaire heights 31 1/2 - 39 1/4				
		Door	A	B Anch. unit
99 635	Emergency lighting battery 6.0W	✓	7 1/2	32 79 818

Type:

BEGA Product:

Project:

Voltage:

Color:

Options:

Modified:

