


BEGA

Photometric Filename: 99778.ies

TEST: BE_99778
TEST LAB: BEGA
DATE: 11/10/2015
LUMINAIRE: 99 778
LAMP: 29.4W LED




Characteristics

IES Classification	N.A.
Longitudinal Classification	N.A.
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	398
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	12
Total Luminaire Watts	34
Ballast Factor	1.00
Upward Waste Light Ratio	0.51
Max. Cd.	156.2 (360H, 90V)
Max. Cd. (<90 Vert.)	151.8 (360H, 87.5V)
Max. Cd. (At 90 Deg. Vert.)	156.2 (39.2%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	151.8 (38.1%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)

Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	0.3	N.A.	0.1
FM (30-60)	20.5	N.A.	5.2
FH (60-80)	83.8	N.A.	21.1
FVH (80-90)	65.8	N.A.	16.5
BL (0-30)	0.1	N.A.	0.0
BM (30-60)	2.6	N.A.	0.7
BH (60-80)	12.4	N.A.	3.1
BVH (80-90)	10.2	N.A.	2.6
UL (90-100)	77.3	N.A.	19.4
UH (100-180)	124.9	N.A.	31.4
Total	397.9	N.A.	100.0

BUG Rating B0-U3-G1



Mounting Height = 2.9 ft. Grid Spacing = 5 ft.

*Using 99 624 system bollard tube

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

4/23/2018

