

**Application**  
System bollard head with 360° light distribution. Simply order the bollard head and also the required bollard tube in various heights and options. Both modules can be joined together easily and quickly during installation.

**Materials**  
Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Clear safety glass  
Reflector made of pure anodized aluminum  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
Interlocking stainless steel mounting mechanism

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Effective projection area: xxx sq. ft.  
Weight: 10.1 lbs

<b>Electrical</b>	
Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	16.5 W
System wattage	19.8 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1,838 lumens (4000K)
LED service life (L70)	60,000 hours

**LED color temperature**  
4000K - Product number + **K4 (EXPRESS)**  
3500K - Product number + **K35**  
3000K - Product number + **K3 (EXPRESS)**  
2700K - Product number + **K27**


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:  
BEGA Product:  
Project:  
Modified:

**Compatible bollard tube (select one)**  
**99 615** No access door - height 14 ½  
**99 622** With access door - height 32 ⅝  
**99 644** Integral floodlight  
**99 626** Integral GFCI outlet  
**99 658** Passive infrared motion sensor  
**99 635** Emergency lighting battery  
See individual bollard tube spec sheet for details.



System bollard head · shielded with reflector · 360°			
	LED	A	B
99 856	16.5 W	7 ½	7 ¼

