

Surface washers · asymmetrical light distribution

**Post construction:** One piece extruded aluminum, 1/8" wall thickness internally welded to a die-cast base plate cover.

**Enclosure:** One piece die-cast aluminum housing connected to the post/pole by a two piece, die-cast aluminum knuckle. The knuckle has infinite adjustability from 0° to 90° and is secured by one stainless steel fastener. Fully gasketed using a one piece molded high temperature silicone gasket and provided with a pure anodized matte aluminum reflector. Molded 1/4" thick etched tempered glass secured by a one piece die-cast aluminum frame secured to the housing with four stainless steel captive fasteners. Die castings are marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy.

**Electrical:** 15.6W LED luminaire, 18 total system watts, -30°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 3000K with an 85 CRI. Available in 4000K (85 CRI); add suffix K4 to order.

**Anchor base:** Pole Mount; Mounts to #79818 anchorage kit (supplied).

**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.


**CSA** certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

**Weight:** 34.3 lbs.

**EPA (Effective projection area):** 0.81 sq. ft.

**Luminaire Lumens:** 1754

Type:  
BEGA Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:



Pole mounted · asymmetrical					
	Lamp	A	B	C	Anchorage
99868	15.6W LED	10 1/4	98 1/2	12 1/2	79818